

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 June 2006 (22.06.2006)

PCT

(10) International Publication Number
WO 2006/065924 A2

(51) International Patent Classification:
B61D 45/00 (2006.01)

(21) International Application Number:

PCT/US2005/045277

(22) International Filing Date:

14 December 2005 (14.12.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/636,014 15 December 2004 (15.12.2004) US

(71) Applicant (for all designated States except US):
MARHALO HOLDINGS LIMITED [CA/CA]; 45599
Pioneer Drive, Chilliwack, British Columbia V2R 2T2
(CA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WIEBE, Marvin,
Ben** [US/US]; c/o Marhalo Holdings Limited, 45599
Pioneer Drive, Chilliwack, British Columbia V2R 2T2
(CA).


(74) Agent: **BRODY, Christopher, W.**; CLARK & BRODY,
1090 Vermont Avenue, N.W., Suite 250, Washington, DC
2006 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,

[Continued on next page]

(54) Title: STACKED CARGO SECURING DEVICE AND METHOD OF USE



(57) Abstract: A load securing device for stacked cargo comprises a body member having contact surfaces adapted to engage a side portion of each of a pair of stacked cargo items. One end of a flexible member such as a strap is attached to the body member. The flexible member extends through a space created between the stacked items, with its other end being secured to a carrier supporting the stacked items. Optimally, and when expecting forces to be applied to both sides of the stacked items, a load securing device is placed on either side of the stacked items so that forces arising during the transport of the stacked items are resisted in both directions.

WO 2006/065924 A2



RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*